



# HDPE KRM 60

HIGH DENSITY POLYETHYLENE

## DESCRIPTION

**HDPE KRM 60** is a high density polyethylene compound (BLACK) produced by the ultimate KOREMPLAST's technology. Carbon black gives outstanding UV resistance.

## APPLICATION

Extrusion / Blow Moulding

## TYPICAL PROPERTIES

| PROPERTY         | METHOD   | UNIT     | RANGE        |
|------------------|----------|----------|--------------|
| M.F.I. (2.16 kg) | ISO 1133 | g/10 min | 0.20- 0.45   |
| Density          | ISO 1183 | g/cm3    | 0.955 -0.972 |
| Carbon Black     | ISO 6964 | %        | 2.00 – 3.00  |

## NOTES

- It is recommended to dry the material before use;
- Not to be used for specific applications;
- Not for pressure pipes;
- Koremplast is not responsible for the finished products.

**KOREMPLAST** S.P.A.

Sede legale: Via L.Einaudi 24 - 61032 Fano (PU)

Sede operativa: Via Ca' Maspino snc - 61048 Sant'Angelo in Vado (PU) - Italy

Tel. +39 0722 810032 Fax +39 0722 818413

E-mail: [koremplast@koremplast.com](mailto:koremplast@koremplast.com) Website: [www.koremplast.com](http://www.koremplast.com)