



**KOREMPLAST**

## PP KRM 0501

### DESCRIPTION

**PP KRM 0501** is polypropylene compound (BLACK) produced by the ultimate KOREMPLAST's technology.

### APPLICATION

Injection

### TYPICAL PROPERTIES

| PROPERTY                 | METHOD   | UNIT              | RANGE         |
|--------------------------|----------|-------------------|---------------|
| M.F.I. (2.16 kg a 230°C) | ISO 1133 | g/10 min          | 8-12          |
| Density                  | ISO 1183 | g/cm <sup>3</sup> | 0.950 – 0.960 |
| IZOD                     | ISO 180  | KI/m <sup>2</sup> | > 25          |
| ASH*                     | ISO 6964 | %                 | < 7           |
| Color                    |          |                   | BLACK         |

\*ASH present as intrinsic characteristic of the material

### NOTES

- It is recommended to dry the material before use;
- Not to be used for specific applications;
- Koremplast is not responsible for the finished products.

**KOREMPLAST** s.r.l. UNIPERSONALE

Via Ca' Maspino snc, 61048 Sant' Angelo in Vado (PU) - ITALIA

Tel. +39 - 0722 810032

Email: [koremplast@koremplast.com](mailto:koremplast@koremplast.com) • Website: [www.koremplast.com](http://www.koremplast.com)